

VRLA AGM Battery

12IP9VA[12V9Ah]



General Features

- Designed floating charging service life: 8 years (25°C)
- Sealed and maintenance free operation
- Safety valve installation for explosion proof
- Low self-discharge characteristic
- Wide operating temperature range from 0°C~40°C
- Lead Aluminum calcium Tin alloy high energy, prevent corrosion


Application

- DC power supply
- Medical equipments
- UPS/EPS power supply
- Emergency lighting systems
- Alarm and security systems

Physical Specifications

Nominal Voltage	Nominal Capacity (20HR)	Dimension				Weight ±2%	Internal Resistance (In full charge status)	Standard Terminals
		L	W	H	TH			
12V	9.0AH	151±2mm	65±2mm	93.5±2mm	99.5±2mm	Approx2.48kg (5.5lbs)	≈20.3 mΩ	F01/F02 (standard)

Dimensions



Constant-Voltage Charge

Rated Capacity	
20 hour rate (0.425A)	9.00AH
10 hour rate (0.85A)	8.36AH
5 hour rate (1.44A)	7.55AH
27 minute rate(8.5A)	4.05AH
7 minute rate (25.5A)	3.15AH
Capacity affected by Temperature	
40°C(104°F)	103%
25°C(77°F)	100%
0°C(32°F)	86%

Cycle Application

1. Limit initial current less than 2.7A.
2. Charge until battery voltage (under charge) reaches 14.1V to 14.4V at 25°C(77°F).
3. Hold at 14.1V to 14.4V until current drop to under 0.051A for at least 3 hours.
4. Temperature compensation coefficient of charging voltage is -30mV/°C.

Standby Service

1. Hold battery across constant voltage source of 13.6to 13.8 volts with current limit 2.7A continuously .When held at this voltage , the battery will seek its own current level and maintain itself in a fully charge status.
2. Temperature compensation coefficient of charging voltage is -18mV/°C.


NOTE : The battery should be charged within 6 months of storage, Otherwise, permanent loss of capacity might occur as a result of sulfation

Battery Discharge Table


End Voltage (V)	Minute (M)				Hour (H)							
	10	15	30	45	1	1.5	2	3	5	8	10	20
Constant Current Discharge Data Sheet (@25°C) Unit: A												
9.6V	22.2	17.3	8.90	6.26	5.30	4.23	3.15	2.38	1.53	1.013	0.813	0.438
9.9V	21.2	16.6	8.48	6.05	5.18	4.13	3.07	2.31	1.48	0.994	0.806	0.433
10.2V	20.2	15.8	8.07	5.84	5.05	4.03	3.00	2.26	1.45	0.974	0.797	0.429
10.5V	20.0	15.7	8.00	5.78	5.02	3.96	2.88	2.19	1.42	0.957	0.789	0.425
10.8V	19.7	15.5	7.92	5.71	4.98	3.87	2.77	2.10	1.39	0.950	0.782	0.421
Constant Power Discharge Data Sheet (@25°C) Unit: W												
9.6V	267	216	122	86.7	65.1	50.0	37.6	26.8	17.7	12.3	9.78	5.27
9.9V	255	207	117	83.8	63.5	48.7	36.7	26.2	17.3	12.1	9.69	5.22
10.2V	242	196	111	81.0	62.1	47.5	35.8	25.6	16.8	11.9	9.59	5.17
10.5V	235	191	109	79.1	61.0	46.9	35.2	24.9	16.6	11.8	9.45	5.09
10.8V	226	185	106	77.1	60.1	46.2	34.8	24.5	16.4	11.7	9.29	5.02

Performance Characteristics


Charge Characteristics (25°C/77°F)




Discharge Characteristic (25°C/77°F)




Cycle Life in Relation to Depth of Discharge




Temperature vs Float Life



Capacity Curve At Different Temperature



Self Discharge Characteristics



☆The datasheet subjects to change without prior notice, please contact with us if have any questions.